

BB-2590 LITHIUM-ION BATTERY PACK

9.3Ah STANDARD

Part number: 430856 NSN: 6130-99-241-7950

This new and enhanced Pack from EnerSys ABSL's military product range provides a high performance solution allowing integration into existing platforms.

SPECIFICATIONS

Technical Data:

Technology	Lithium-ion
Voltage Range	20-32.8V (24V mode) 10–16.4V (12V mode)
Capacity	9.3 Ah (28.8V Nominal) 18.6 Ah (14.4V Nominal)
Charging	16.8 V @ 3A Maximum
Max Discharge Current	10 ± 0.5A (24V mode) / 20 ±1A (12V mode) continuous
Length	111.5 mm
Width	62.0 mm
Height	126.7 mm
Weight	1.34 Kg
Operating Temperature	-30 °C to +70 °C
Storage Temperature Range	-40 °C to +70 °C
Application	Dismounted soldier


Features & Benefits:


- Extended battery life
- Improved internal power manager
- Improved cycle life
- Increased capacity
- Extended temperature range
- Rapid charging capability
- High-rate discharge
- Lightweight
- Waterproof
- RoHS compliant
- Connector SC-C-179495 compliant
- High specific energy (200 Wh/Kg)


Safety Features:

- Cell overvoltage
- Cell undervoltage
- Over-charge current
- Over-discharge current
- Over-temperature
- Cell mismatch
- Cell balancing
- LCD state of charge indicator

Dimensions:









Denchi Power Ltd Denchi House, Thurso Business Park, Thurso, Caithness, KW14 7XW, UK Tel: +44 (0) 1847 808 000 E: enquiries@denchipower.com